

# WINDOW CURTAIN TRACK

## MACTRAC DELUXE (MAC4)

  
**mactrac**  
the *architects* choice

### Drawing options

Hand drawn, wand drawn or cord drawn.

### Size

23.5mm x 19.0mm, profile wall thickness 1.25mm, available up to 6m lengths in head and face fix on brackets (Mac3 A).

In lengths beyond 6m, tracks can be joined without interrupting the travel of the glides.

### Profile

Extruded aluminium structural channel section with lipped glide channel below. An extra leg extends horizontally out from the top of the structural channel to provide head fixing either directly to the soffit, or used with proprietary brackets as a method of face fixing the track.

### Glides

Solid glide manufactured from high density polyethylene, waisted in section to slide between the lipped channel with a closed ring beneath. A hook hangs from the ring from which the curtain is suspended.

16 glides are supplied per metre of Mactrac Deluxe.

### Travel

The curtain travels freely around all sections of the track.

### Corners

Mactrac Deluxe can be bent to a 170mm radius.

### Finishes

Natural anodised and white, ivory and rimu powdercoated are standard, and a wide range of alternative powdercoated colours is available on request.

### Fittings

Standard fittings available are :

P2 (50mm), P3 (75mm), P4 (100mm), P5 (125mm) brackets and are spaced 700mm apart

There is also provision for head fixing at 200mm centres

End stops

Pulley blocks, master carriers, overlap and underlap arms are supplied for cord drawn tracks

End return brackets


Components for multiple track systems

### Fixings

Approved fixings for solid concrete, brick, timber walls / ceiling and cavity walls / ceilings are used.



### PROFILE



Proudly made by

**TETRAL**

Tetral Industries Limited  
Christchurch  
New Zealand  
Phone (03) 379 2400  
Fax (03) 365 4979  
www.mactrac.co.nz